

IC-i3t-DVW-ACIOVW

The IC-i3t-DVW-ACIOVW is an in-ceiling mount vandal proof 20m IR dome camera.

The IC-i3t-DVW-ACIOVW has a 3 MegaPixel Aptina CMOS and a Texas Instruments chipset that delivers full WDR (100dB) performance

The IC-i3t-DVW-ACIOVW also has extra features like alarm I/O's, audio support, Micro SD & BNC Spot Out.



Main Features

- 1/3" Aptina CMOS
- Texas Instruments Chipset
- 3 Megapixel
- In-Ceiling Mount Design
- H.264 & MJPEG Video Compression
- 3MP @ 15FPS - 1080P/720P/D1 @ 25/30FPS
- 3.3-12mm F1.4 Vari-Focal Lens
- Lens Angle = H:91.2°(Wide)-25.5°(Tele)
- Onvif (Ver 2) Profile S Compliant
- Up to 20m IR Distance
- Min Illumination: Colour: 0.1Lux/F1.4, B/W: 0.01Lux/F1.4; 0Lux/F1.4(IR on)
- BLC / HLC / WDR (100dB)
- 3D Noise Reduction
- Up to 20 Users Network Access
- RJ-45 (10/100Base-T) Network Port
- Network Features: IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
- FREE SmartICRSS Client Software for Windows and Mac OS X
- ICRSS Pro Application for iOS (iPhone / iPad), Android (Smart Phone and Tablets) & Windows Phone
- Active X and Quick Time Web Browser
- 1 channel in/out Audio Interface
- Micro SD Slot (Max 64GB)
- 1 Alarm Input / 1 Alarm Output
- IP66 Weatherproof
- IK10 Vandal Proof Rating
- 12vDC / 24vAC / <8W
- PoE (802.3af)
- Dimensions: Φ 146mm \times 139.5mm
- Weight: 1.18KG



www.icrealtime.net

European Head Office

IC Realtime,
12 Knockmitten Lane,
Western Industrial Estate,
Dublin 12, Ireland.
Phone 0818 903 365
(ROI National call rate)
Phone +353 (0) 1 4268275
Fax +353 (0) 1 4196245
Email info@icrealtime.ie

UK Office

IC Realtime UK
Surrey Technology Centre,
40 Occam Road,
Guildford GU2 7YG,
United Kingdom
Phone +44 (0) 1483 685460
Fax +44 (0) 1483 685461
Email sales@icrealtime.co.uk

USA Head Office

IC Realtime, LLC,
3050 N Andrews Ave EXT,
Pompano Beach, FL 33064, USA
Phone (954) 772-5327
Toll (866) 997 9009
Fax (866) 860-3860
Email info@icrealtime.com

USA West Coast Office

IC Realtime West Coast,
14180 W Van Buren Street,
Suite B-105, Goodyear,
AZ 85338, USA
Phone (602) 910 3432
Fax (602) 626 3545
Email info@icrealtime.com

Model	IC-i3t-DVW-ACIOVW
VIDEO	
Image Sensor	1/3" Aptina CMOS
Chipset	Texas Instruments
Resolution	3 MegaPixel
Effective Pixels	2052(H) x 1536(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3-1/10000
Min. Illumination	Colour: 0.1Lux/F1.4, B/W: 0.01Lux/F1.4; 0Lux/F1.4(IR on)
S/N Ratio	>50dB
Video Output	1 Port
ENCODE	
Compression	H.264/ MJPEG
Resolution	3.0M(2048x1536)/1080P(1920x1080)/720P(1280x720)/D1(704x576)/CIF(352x288)
FPS - Main Stream	3M(1-15fps)/1080P/720P(1 - 25/30fps)
FPS - Sub Stream	D1/CIF(1 - 25/30fps)
Bit Rate	H.264: 32K - 8192Kbps
FEATURES	
Max IR Distance	20m
Day/Night	Auto(ICR) / Color / B/W
Backlight Compensation	BLC / HLC / WDR (100dB)
White Balance	Auto
Gain Control	Auto/Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
LENS	
Focal Length	3.3-12mm
Max Aperture	F1.4
Focus Control	Manual
Angle of View	H: 91.2°(Wide)-25.5°(Tele)
Lens Type	Manual /Auto Iris (DC)
Mount Type	Board-in Type
NETWORK	
Ethernet Port	RJ-45 (10/100Base-T)
Wi-Fi	N/A
Network Function	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
ONVIF	ONVIF Profile S
Max Online Users	20
AUDIO	
Interface	1/1 channel In/Out
Compression	G.711a / G.711u (32kbps) / PCM (128kbps)
Other Interfaces	
Memory Slot	Micro SD, Max 64GB
RS-485	N/A
Alarm	1/1 channel In/Out
GENERAL	
Power Supply	DC12V/AC24V, PoE(802.3af)
Power Consumption	<8W
Working Environment	-10°C~+60°C, 10%-90%
IP Rating	IP66
Vandal Resistance	IK10
Dimensions	Φ146mm×139.5mm
Weight	1.18Kg