

# Fusion

Versatile Technology

## FUSION-3s-208

The FUSION-3s-208 is a 1080P real time (200fps) 8 channel 1U (desktop) Tri-Tech recorder that combines 3 video technologies (IP, HDCVI & analogue).

This 8 channel recorder with internal capacity for 2 hard drives has 8 self-adaptive BNC inputs, that can process either an SD analogue or a HDCVI signal. Its embedded HD processor can also facilitate 2 IP channels (16Mbps).

Using the latest HD over coax technology (HDCVI) combined with powerful networking capabilities; this future proof recorder is ideally suited for existing coaxial & Cat 5 installations, saving you valuable deployment time whilst delivering real time 1080P recording on every channel.

### PERFORMANCE

Resolution	IP	1080P	(1-25fps)
	HDCVI	1080P	(1-25fps)
	Analogue	960H	(1-25fps)
IP Recording	16Mbps		
Processor	Dual Core Embedded		
Video Compression	H.264, MJPEG		
Audio Compression	G711A		



### SOFTWARE

OS	Embedded Linux (ICR OS)
Video Detection	Motion Detection, Video Loss & Camera Masking
Smart Search	Yes
Simultaneous Playback	All Channel
Max User Access	128
Network Functions	Alarm Server, DDNS, DHCP, DNS, Email, FTP, HTTP, IP Filter, IPv4, IPv6, PPPoE, RTSP, SMTP, TCP/IP, UDP, UPnP
IPC Support	Onvif, Axis, Bosch, Hikvision, Panasonic, Pelco, Samsung, Sony and many more...
Smart Phone / Tablet	ICRSS Pro & ICView
PC / Mac Software	SmartICRSS & Web Browser
Push Notifications	Yes
ICDDNS	Yes
P2P	Yes
Extra Stream	Yes
Onvif	Yes
ARC Integration	Yes

### CONNECTIVITY

Total Video Channels	8
IP Channels	2
HDCVI Channels	8
Analogue Channels	8
Audio Input (RCA)	4
Audio Output (RCA)	1
2 Way Audio Supported	Yes
Alarm Inputs	16
Alarm Outputs	3
HDMI	1
VGA	1
BNC (Master)	0
PoE IPC Ports	0
10/100M RJ45 Port	0
10/100/1000M RJ45 Port	1
RS-485	1
RS-232	n/a
USB Ports	2 (1 Rear)

### STORAGE

SATA Ports	2
RAID	n/a
eSATA Port	0
Backup Methods	USB & Network

### ENVIRONMENTAL

Case Size	1U Desktop (375mm)
Dimensions (mm)	375 (W) x 285 (D) x 55 (H)
Power Supply	12V DC / 5 Amp
Power Consumption	15W (without HDD)
Working Environment	-10°C-+55°C/10%-90%RH/86-106kpa
Weight	2.35KG (without HDD)
Certification	CE, FCC



**European Head Office**  
 IC Realtime,  
 12 Knockmitten Lane,  
 Western Industrial Estate,  
 Dublin 12,  
 Ireland

**UK Office**  
 IC Realtime UK  
 Surrey Technology Centre,  
 40 Occam Road,  
 Guildford GU2 7YG,  
 United Kingdom

**USA Head Office**  
 IC Realtime, LLC,  
 3050 N Andrews Ave EXT,  
 Pompano Beach,  
 FL 33064,  
 USA

**USA West Coast Office**  
 IC Realtime West Coast,  
 14180 W Van Buren Street,  
 Suite B-105, Goodyear,  
 AZ 85338,  
 USA