

wave

RELIABLE HD

WAVE-2s-108

The WAVE-2s-108 is an 8 channel Tri-Tech recorder that combines 3 video technologies (720P HDCVI, 960H analogue CVBS and 1080P IP). It has a total of 8 channels with 8 BNC inputs and its embedded processor can facilitate 2 IP channels. It comes in a 1U desktop case (260x220x40mm) with 1 internal SATA port. It supports all channel playback with backup methods including USB and network.

The Wave range of recorders utilises Hdctv approved HDCVI 2.0 technology. HDCVI 2.0 can use existing coaxial or UTP cable (with baluns) to deliver up to 1080P resolution which saves you valuable deployment time and reduces waste.

This technology will allow transmission of video, audio and data (OSD & PTZ Controls) over a staggering 600m of 75-5 coaxial cable (25fps/720P Resolution). It is also latency free for instant live view, plug & play and costs the same as analogue.

PERFORMANCE

Resolution	IP	1080P	(1-25fps)
	HDCVI	720P	(1-15fps)
	Analogue	960H	(1-25fps)
IP Recording	8Mbps		
Processor	Dual Core Embedded		
Video Compression	H.264		
Audio Compression	G711A		



SOFTWARE

OS	Embedded Linux (ICR OS)
Video Detection	Motion Detection, Video Loss & Camera Masking
Smart Search	Yes
Simultaneous Playback	All Channel
Max User Access	128
Network Functions	Alarm Server, DDNS, DHCP, DNS, Email, FTP, HTTP, IP Filter, IPv4, IPv6, PPPoE, RTSP, SMTP, TCP/IP, UDP, UPnP
IPC Support	Onvif, Axis, Bosch, Hikvision, Panasonic, Pelco, Samsung, Sony and many more...
Smart Phone / Tablet	ICRSS Pro & ICView
PC / Mac Software	SmartICRSS & Web Browser
Push Notifications	Yes
ICDDNS	Yes
P2P	Yes
Extra Stream	Yes
Onvif	Yes
ARC Integration	Yes

CONNECTIVITY

Total Video Channels	8
IP Channels	2
HDCVI Channels	8
Analogue Channels	8
Audio Input (RCA)	1
Audio Output (PCA)	1
2 Way Audio Supported	Yes
Alarm Inputs	n/a
Alarm Outputs	n/a
HDMI	1
VGA	1
BNC (Master)	0
PoE IPC Ports	0
10/100M RJ45 Port	1
10/100/1000M RJ45 Port	0
RS-485	1
USB Ports	2 (1 Rear)

STORAGE

SATA Ports	1
RAID	n/a
eSATA Port	0
Backup Methods	USB, Network

ENVIRONMENTAL

Case Size	1U Desktop
Dimensions (mm)	260 (W) x 220 (D) x 40 (H)
Power Supply	12V DC / 2 Amp
Power Consumption	10W (without HDD)
Working Environment	-10°C - +55°C / 10% - 90%RH / 86-106kpa
Weight	1.0KG (without HDD)
Certification	CE, FCC



European Head Office
 IC Realtime,
 12 Knockmitten Lane,
 Western Industrial Estate,
 Dublin 12,
 Ireland

UK Office
 IC Realtime UK
 Surrey Technology Centre,
 40 Occam Road,
 Guildford GU2 7YG,
 United Kingdom

USA Head Office
 IC Realtime, LLC,
 3050 N Andrews Ave EXT,
 Pompano Beach,
 FL 33064,
 USA

USA West Coast Office
 IC Realtime West Coast,
 14180 W Van Buren Street,
 Suite B-105, Goodyear,
 AZ 85338,
 USA