

wave

RELIABLE HD

WAVE-3s-116

The WAVE-3s-116 is a 16 channel Tri-Tech recorder that combines 3 video technologies (1080N / 720P HDCVI, 960H analogue CVBS and 5MP IP). It has a total of 18 channels with 16 BNC inputs and its embedded processor can facilitate an additional 2 IP channels. It comes in a 1U desktop case (260x220x40mm) with 1 internal SATA port. It supports all channel playback with backup methods including USB and network.

The Wave range of recorders utilises HDcctv approved HDCVI 2.0 technology. HDCVI 2.0 can use existing coaxial or UTP cable (with baluns) to deliver up to 1080P resolution which saves you valuable deployment time and reduces waste.

This technology will allow transmission of video, audio and data (OSD & PTZ controls) over a staggering 600m of 75-5 coaxial cable (25fps/720P Resolution). This technology is latency free for instant live view, plug & play and costs the same as analogue.



PERFORMANCE

Resolution	IP	5MP	(1-25fps)
	HDCVI	1080N	(1-15fps)
		720P	(1-15fps)
	Analogue	960H	(1-25fps)
IP Recording		72Mbps	
Processor		Dual Core Embedded	
Video Compression		H.264	
Audio Compression		G.711	

SOFTWARE

OS	Embedded Linux (ICR OS)
Video Detection	Motion Detection, Video Loss & Camera Masking
Smart Search	Yes
Simultaneous Playback	All Channel
Max User Access	128
Network Functions	Alarm Server, DDNS, DHCP, DNS, Email, FTP, HTTP, IP Filter, IPv4, IPv6, PPPoE, RTSP, SMTP, TCP/IP, UDP, UPnP
IPC Support	Onvif, Axis, Bosch, Hikvision, Panasonic, Pelco, Samsung, Sony and many more...
Smart Phone / Tablet PC / Mac Software	ICRSS Pro & ICView
Push Notifications	SmartICRSS & Web Browser
ICDDNS	Yes
P2P	Yes
Extra Stream	Yes
Onvif	Yes
ARC Integration	n/a

CONNECTIVITY

Total Video Channels	18
IP Channels	2
HDCVI Channels	16
Analogue Channels	16
Audio Input (RCA)	1
Audio Output (RCA)	1
2 Way Audio Supported	Yes
Alarm Inputs	n/a
Alarm Outputs	n/a
HDMI	1
VGA	1
BNC (Master)	0
PoE IPC Ports	0
10/100M RJ45 Port	1
10/100/1000M RJ45 Port	0
RS-485	1
USB Ports	2 (1 Rear)

STORAGE

SATA Ports	1
RAID	n/a
eSATA Port	0
Backup Methods	USB, Network

ENVIRONMENTAL

Case Size	1U Desktop
Dimensions (mm)	260 (W) x 220 (D) x 40 (H)
Power Supply	12V DC / 2 Amp
Power Consumption	10W (without HDD)
Working Environment	-10°C-+55°C/10%-90%RH/86-106kpa
Weight	1.0KG (without HDD)
Certification	CE, FCC



• **European Head Office**
 • IC Realtime,
 • 12 Knockmitten Lane,
 • Western Industrial Estate,
 • Dublin 12,
 • Ireland

• **UK Office**
 • IC Realtime UK
 • Surrey Technology Centre,
 • 40 Occam Road,
 • Guildford GU2 7YG,
 • United Kingdom

• **USA Head Office**
 • IC Realtime, LLC,
 • 3050 N Andrews Ave EXT,
 • Pompano Beach,
 • FL 33064,
 • USA

• **USA West Coast Office**
 • IC Realtime West Coast,
 • 14180 W Van Buren Street,
 • Suite B-105, Goodyear,
 • AZ 85338,
 • USA