

Zenon

ZENON-1s-BF4-IXO



IP Technology



4MP Resolution



Intelligent Detection



80m IR

The ZENON-1s-BF4-IXO is an intelligent 4MP long range day/night IR Bullet Camera. As for optics this camera uses an accurate 6mm fixed lens with a 80m IR viewing distance.

It uses an Ambarella chipset which delivers high quality low bandwidth video streaming and can also provide 3 video streams simultaneously. The Ambarella chipset has built in intelligent functions such as Tripwire and the camera also has 120dB WDR as standard.



PERFORMANCE

Image Sensor	CMOS (1/3")
Chipset	Ambarella
Effective Pixels	2688(H) x 1520(V)
Compression	H.264/MJPEG
Resolution	4MP (1-20fps) 3MP (1-25fps)
Streams	3
Bit Rate	32-10Mbps (H.264)

Backlight Compensation	BLC / HLC
Wide Dynamic Range	WDR (120dB)
White Balance	Auto / Manual
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Corridor Mode	Yes

LENS

Focal Length	6mm
Max Aperture	F2.0
Angle of View	H: 55°

DAY / NIGHT

Min. Illumination	Colour	0.01 Lux @ F2.0
	IR On	0 Lux @ F2.0
Day/Night	Auto (ICR) / Colour / B/W	
IR Distance	80m	

CONNECTIVITY

Ethernet	1 RJ45 (10/100Base-T)
BNC Output (CVBS)	0
Alarm Input	0
Alarm Output	0
Audio Input	0
Audio Output	0
RS-485	0
Memory Slot	0

SOFTWARE

Network Functions	IPv4/ IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x
-------------------	---

Smart Phone/Tablet PC / Mac Software	ICRSS Pro / ICView Smart ICRSS / Web Browser Onvif, PSIA
--------------------------------------	--

Intelligent Functions	Tripwire, Intrusion, Abandoned / Missing Object, Scene Change, Audio Detect & Face Detect
-----------------------	---

Trigger Mode	Manual / Auto (alarm triggered)
--------------	---------------------------------

Trigger Event	Recording, Email, Snapshot, Relay
---------------	-----------------------------------

ENVIRONMENTAL

Power Consumption	12vDC / PoE (802.3af) <5W
Working Environment Protection	-30°C - 60°C / Less than 95% RH IP67
Dimensions Weight	Ø90.4(mm) x 241.8 (mm) 0.61kg

ACCESSORIES (OPTIONAL)

BASE-135-W	Junction Base
MNT-CRM3	Corner Mount
MNT-PM152	Pole Mount



• European Head Office
 • IC Realtime,
 • 12 Knockmitten Lane,
 • Western Industrial Estate,
 • Dublin 12,
 • Ireland

• UK Office
 • IC Realtime UK
 • Surrey Technology Centre,
 • 40 Occam Road,
 • Guildford GU2 7YG,
 • United Kingdom

• USA Head Office
 • IC Realtime, LLC,
 • 3050 N Andrews Ave EXT,
 • Pompano Beach,
 • FL 33064,
 • USA

• USA West Coast Office
 • IC Realtime West Coast,
 • 14180 W Van Buren Street,
 • Suite B-105, Goodyear,
 • AZ 85338,
 • USA