

SIROCCO

BREATH-taking PERFORMANCE



SIROCCO-4s-432

The SIROCCO-4s-432 is a 4K H.265 32 channel Network Video Recorder (NVR). It has a powerful embedded dual-core processor providing up to 12 megapixel (including 4K) resolution per channel and a global recording capacity of 192Mbps.

The SIROCCO-4s-432 is housed in a 1.5U rack mountable case with 4 internal SATA ports. It comes with 2 x HDMI & 1 x VGA video outputs and supports backup methods via USB 3.0, eSata, internal burner and network.

The SIROCCO-4s-432 has two independent 1GB ethernet ports allowing for IP cameras to be separated effectively on the network.

This recorder is provided license free, Onvif compatible and supports various 3rd party IP camera vendors.

PERFORMANCE

Resolution	IP	12 MegaPixel / 4K
	HDCVI	Not applicable
	Analogue	Not applicable
IP Recording		192Mbps
Bit Rate Support		1-20Mbps Per Channel
Processor		Dual Core Embedded
Video Compression		H.265, H.264, MJPEG



SOFTWARE

OS	Embedded Linux (ICR OS)
Smart Features	Yes
Fisheye Dewarp Support	Yes - Live View Only
Video Detection	Motion Detection, Video Loss & Camera Masking
Smart Search	Yes
Simultaneous Playback	4 channel (4MP, 20fps)
Max User Access	128
Network Functions	Alarm Server, DDNS, DHCP, DNS, Email, FTP, HTTP, IP Filter, IPv4, IPv6, PPPoE, RTSP, SMTP, TCP/IP, UDP, UPnP
IPC Support	Onvif, Axis, Bosch, Hikvision, Panasonic, Pelco, Samsung, Sony and many more...
Smart Phone / Tablet	ICRSS Pro & ICView
PC / Mac Software	SmartICRSS & Web Browser
Push Notifications	Yes
ICDDNS	Yes
P2P	Yes
Extra Stream	Yes
Onvif	Yes

CONNECTIVITY

Total Video Channels	32
IP Channels	32
HDCVI Channels	0
Analogue Channels	0
Audio (IP)	Yes
Audio Output (RCA)	1
2 Way Audio Supported	Yes
Alarm Inputs	16
Alarm Outputs	6
HDMI - 4K (3840x2160)	2
VGA	1
BNC (Master)	0
PoE IPC Ports	0
10/100M RJ45 Port	0
10/100/1000M RJ45 Port	2
RS-485	1
RS-232	1
USB 2.0 Port(s)	1 (Front)
USB 3.0 Port(s)	2 (Rear)

STORAGE

SATA Ports	4 HDD or 3 HDD + 1 Burner
RAID	n/a
eSATA Port	1
Backup Methods	USB, eSata, Internal Burner and Network

ENVIRONMENTAL

Case Size	1.5U Rack Mountable
Dimensions (mm)	440 (W) x 405 (D) x 76 (H)
Power Supply	AC 100-240 V, 50/60 Hz
Power Consumption	17W (without HDD)
Working Environment	-10°C ~ +55°C / 10% ~ 90%RH / 86-106kpa
Weight	4.35KG (without HDD)
Certification	CE, FCC



European Head Office
 IC Realtime,
 12 Knockmitten Lane,
 Western Industrial Estate,
 Dublin 12,
 Ireland

UK Office
 IC Realtime UK
 Surrey Technology Centre,
 40 Occam Road,
 Guildford GU2 7YG,
 United Kingdom

USA Head Office
 IC Realtime, LLC,
 3050 N Andrews Ave EXT,
 Pompano Beach,
 FL 33064,
 USA

USA West Coast Office
 IC Realtime West Coast,
 14180 W Van Buren Street,
 Suite B-105, Goodyear,
 AZ 85338,
 USA